

Veriopt Theories

April 17, 2024

Contents

1 Graph Type Class Instantiations	1
1.1 Equal Instance	1

1 Graph Type Class Instantiations

```
theory
  IRGraphSort
imports
  Graph.IRGraph
begin
```

An *IRGraph* can be treated as an instantiation of various type classes such as the equal type class.

Here we define the instantiations for all type classes of which *IRGraph* belongs.

1.1 Equal Instance

The following is an incorrect definition of equality which is used to allow code generation of the Canonicalization phase. Without this we have to use the values command to generate all possible results of the canonicalization phase.

Note that we should be able to find a correct equality definition in terms of the ids, kind, and stamp function. However, we are yet to find a satisfactory definition as yet.

```
definition IRGraph-equal :: IRGraph ⇒ IRGraph ⇒ bool where
  IRGraph-equal g1 g2 = True
```

```
instantiation IRGraph :: equal
begin
```

```

definition equal-IRGraph :: IRGraph ⇒ IRGraph ⇒ bool where
  equal-IRGraph = IRGraph-equal

instance proof
  fix g1 g2 :: IRGraph
  show equal-class.equal g1 g2 ↔ (g1 = g2)
    apply standard
    unfolding equal-IRGraph-def IRGraph-equal-def
    unfolding as-list-def
    apply transfer
    sorry
qed
end

end
theory ValidationSnippets
imports
  IRGraphSort
  Snippets.Snipping
  Graph.Comparison
  ConditionalElimination.ConditionalElimination
begin

```

notation (latext)
kind (-«-»)

```

intval-mod (IntVal (b1.0::nat) (v1.0::64 word))
(IntVal (b2.0::nat) (v2.0::64 word)) =
(if v2.0 = (0::64 word) then UndefVal
else new-int-bin b1.0 b2.0
(word-of-int
(int-signed-value b1.0 v1.0 smod
int-signed-value b2.0 v2.0)))

```

eval:rem

```

static-test moduloSnippet [(IntVal 32 (1)), (Intval 32
(-2147483648))] (IntVal 32 (1))

```

```

definition test1-initial :: IRGraph where
test1-initial = irgraph [
(0, (StartNode (Some 3) 7), VoidStamp),
(1, (ParameterNode 0), default-stamp),
(2, (ParameterNode 1), default-stamp),
(3, (FrameState [] None None None), IllegalStamp),
(4, (IntegerLessThanNode 2 1), VoidStamp),
(5, (BeginNode 8), VoidStamp),
(6, (BeginNode 13), VoidStamp),
(7, (IfNode 4 6 5), VoidStamp),
(8, (EndNode), VoidStamp),
(9, (MergeNode [8, 10] (Some 16) 18), VoidStamp),
(10, (EndNode), VoidStamp),
(11, (BeginNode 15), VoidStamp),
(12, (BeginNode 10), VoidStamp),
(13, (IfNode 4 11 12), VoidStamp),
(14, (ConstantNode (IntVal 32 (1))), IntegerStamp 32 (1) (1)),
(15, (ReturnNode (Some 14) None), VoidStamp),
(16, (FrameState [] None None None), IllegalStamp),
(17, (ConstantNode (IntVal 32 (2))), IntegerStamp 32 (2) (2)),
(18, (ReturnNode (Some 17) None), VoidStamp)
]

```

```

definition test1-final :: IRGraph where
test1-final = irgraph [
(0, (StartNode (Some 3) 7), VoidStamp),
(1, (ParameterNode 0), default-stamp),
(2, (ParameterNode 1), default-stamp),
(3, (FrameState [] None None None), IllegalStamp),
(4, (IntegerLessThanNode 2 1), VoidStamp),
(5, (BeginNode 8), VoidStamp),
(6, (BeginNode 13), VoidStamp),
(7, (IfNode 4 6 5), VoidStamp),
(8, (EndNode), VoidStamp),
(9, (MergeNode [8, 10] (Some 16) 18), VoidStamp),
(10, (EndNode), VoidStamp),
(11, (BeginNode 15), VoidStamp),
(12, (BeginNode 10), VoidStamp),
(13, (IfNode 19 11 12), VoidStamp),
(14, (ConstantNode (IntVal 32 (1))), IntegerStamp 32 (1) (1)),
(15, (ReturnNode (Some 14) None), VoidStamp),
(16, (FrameState [] None None None), IllegalStamp),
(17, (ConstantNode (IntVal 32 (2))), IntegerStamp 32 (2) (2)),
(18, (ReturnNode (Some 17) None), VoidStamp),
(19, (ConstantNode (IntVal 1 (1))), VoidStamp)
]

```

value runConditionalElimination test1-initial

corollary (*runConditionalElimination test1-initial*) \approx_s *test1-final*
by *eval*

end